

## SOUFRE “CANON CASSÉ”

Product : Broken rolls sulphur  
 Formula : S  
 N° ONU : 1350  
 Type : Cylindrical (30mm diameter and variable length between 30mm and 300mm)  
 Properties : Melting point : 119°C  
 Flash point : 188°C  
 Auto ignition temperature : 232°C  
 Minimum flammable energy : > 1200 milli joule

SPECIFICATION		TYPICAL	METHODS
Sulphur	mini 99,99%	> 99,99	By difference
Moisture	maxi 0,01%	< 0,01	ISO 3426
Product		< 0,001	ISO 3425
Acidity	maxi 0,001%	< 0,001	ISO 3704
Organics	maxi 0,01%	< 0,01%	ISO 2866
Arsenic	maxi 0,00002%	< limit of detection of 0,00001%	Microwave digestion in closed reactor with atomic spectrophotometric absorption in graphic furnace (AAS method)
Selenium	maxi 0,0001%	< limit of detection of 0,00001%	Microwave digestion in closed reactor with atomic spectrophotometric absorption in graphic furnace (AAS method)
Tellerium	maxi 0,0003%	< limit of detection of 0,00001%	Microwave digestion in closed reactor with atomic spectrophotometric absorption in graphic furnace (AAS method)

Uses : Where no dust is required in process  
 Packing : In big bag of 1000 kilograms on pallets  
*Possibilities for other packing on demand*  
 Transport : No dangerous cargo  
 Origin : France