

SOUFRE "CANON"

Product : Sulphur rolls
 Formula : S
 N° ONU : 1350
 Type : Cylindrical (30mm diameter and length 300mm net weight 440g +/- 5g ea).
 Properties : Melting point : 119°C
 Flash point : 188°C
 Auto ignition temperature : 232°C
 Minimum flammable energy : > 1200 milli joule

SPECIFICATION	TYPICAL	METHODS
Sulphur mini 99,99%	> 99,99	By difference
Moisture maxi 0,01%	< 0,01	ISO 3426
Ashes maxi 0,002%	< 0,001	ISO 3425
Acidity maxi 0,001%	< 0,001	ISO 3704
Organics maxi 0,01%	< 0,01%	ISO 2866
Arsenic maxi 0,00002%	< limit of detection of 0,00001%	Microwave digestion in closed reactor with atomic spectrophotometric absorption in graphic furnace (AAS method)
Sélénium maxi 0,0001%	< limit of detection of 0,00001%	Microwave digestion in closed reactor with atomic spectrophotometric absorption in graphic furnace (AAS method)
Tellerium maxi 0,0003%	< limit of detection of 0,00001%	Microwave digestion in closed reactor with atomic spectrophotometric absorption in graphic furnace (AAS method)

Uses : Where no dust is required in process
 Packing : Packed in kraft cartons 25 kg ea.
 On 1200 x1200 pallets 900 kg net
 Stretch-wrapped
Possibilities for other packing on demand

Transport : No dangerous cargo
 Origin : France